


ACE-A615A/B 150 W 1U Type ATX Power Supply



Dimensions (Unit: mm)



Specifications

Input Type	90~264 VAC Full Range					
Output Voltage		+3.3 V	+5 V	+12 V	-12 V	+5 Vsb
	ACE-A615A	10 A (0.3 A min.)	13 A (0.3 A min.)	10 A (1 A min.)	0.5 A (0 A min.)	2.0 A (0 A min.)
	ACE-A615B	10 A (0.1 A min.)	14 A (0.2 A min.)	10 A (0.6 A min.)	0.3 A	2.5 A
Efficiency	ACE-A615A: 68% / ACE-A615B: 85%					
Temperature	Operating: 0°C ~ 50°C, Storage: -20°C ~ 80°C					
MTBF (hrs)	100,000					
Output Connector	ACE-A615A	20-pin ATX, 4-pin 12V CPU, FDD, 3 x HDD				
	ACE-A615B	20+4-pin ATX, 4-pin 12V CPU, 1 x FDD, 2 x HDD, 2 x SATA				
Dimensions (mm)	150 x 81.5 x 40.5					

Ordering Information


Part No.	Description
ACE-A615A-RS-R11	150W AC-DC 1U Flex ATX Power Supply, with PFC/ErP
ACE-A615B-RS-R10	1U Flex ATX 150W Power Supply, 90~264VAC, ErP, CCL, RoHS

1U AC Input AT Type

ACE-916AP 150 W 1U Type AT Power Supply



Dimensions (Unit: mm)



Specifications

Input Type	90 ~ 264 VAC Full Range				
Output Voltage	+5V	+12V	-5V	-12V	+24V
	16 A (1 A min.)	6 A (0.5 A min.)		0.3 A	
Efficiency	68%				
Temperature	0°C ~ 50°C (Operating), -20°C ~ 80°C (Storage)				
MTBF (hrs)	100,000				
Output Connector	P8P9, FDD, 3 x HDD				
Dimensions (mm)	150 x 81.5 x 40.5				

Ordering Information

Part No.	Description
ACE-916AP-RS	150W AC-DC AT Power Supply, with PFC