



AXIOMTEK

IMB500

**Intel® Socket 1151 Core™ i7/ i5/ i3
Processors ATX Industrial
Motherboard**

User's Manual



Disclaimers

This manual has been carefully checked and believed to contain accurate information. Axiomtek Co., Ltd. assumes no responsibility for any infringements of patents or any third party's rights, and any liability arising from such use.

Axiomtek does not warrant or assume any legal liability or responsibility for the accuracy, completeness or usefulness of any information in this document. Axiomtek does not make any commitment to update the information in this manual.

Axiomtek reserves the right to change or revise this document and/or product at any time without notice.

No part of this document may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of Axiomtek Co., Ltd.

CAUTION

If you replace wrong batteries, it causes the danger of explosion. It is recommended by the manufacturer that you follow the manufacturer's instructions to only replace the same or equivalent type of battery, and dispose of used ones.

©Copyright 2016 Axiomtek Co., Ltd.

All Rights Reserved

September 2016, Version A1

Printed in Taiwan

ESD Precautions

Computer boards have integrated circuits sensitive to static electricity. To prevent chipsets from electrostatic discharge damage, please take care of the following jobs with precautions:

- Do not remove boards or integrated circuits from their anti-static packaging until you are ready to install them.
- Before holding the board or integrated circuit, touch an unpainted portion of the system unit chassis for a few seconds. It discharges static electricity from your body.
- Wear a wrist-grounding strap, available from most electronic component stores, when handling boards and components.

Trademarks Acknowledgments

Axiomtek is a trademark of Axiomtek Co., Ltd.

Intel[®] and Celeron[®] are trademarks of Intel Corporation.

Windows[®] is a trademark of Microsoft Corporation.

AMI is a trademark of American Megatrend Inc.

IBM, PC/AT, PS/2, VGA are trademarks of International Business Machines Corporation.

Other brand names and trademarks are the properties and registered brands of their respective owners.

Table of Contents


Disclaimers	ii
ESD Precautions.....	iii
Chapter 1 Introduction.....	1
1.1 Features	2
1.2 Specifications	2
Chapter 2 Board and Pin Assignments	5
2.1 Board Layout.....	5
2.2 Rear I/O.....	6
2.3 Jumper Settings	7
2.3.1 Clear CMOS (JP1)	8
2.3.2 AT/ATX Mode Select (JP2).....	8
2.3.3 COM1 Mode Select (JP3, JP5, JP6).....	9
2.3.4 COM1 Data/Power Select (JP4)	9
2.3.5 COM2 Mode Select (JP7, JP9, JP10).....	9
2.3.6 COM2 Data/Power Select (JP8)	9
2.4 Connectors.....	10
2.4.1 DisplayPort Connector (CN2).....	11
2.4.2 PCI-Express Mini Card Connector (CN3)	11
2.4.3 mSATA Slot (CN4).....	12
2.4.4 Front Panel Header (CN5)	13
2.4.5 GPIO Header (CN6).....	13
2.4.6 PS/2 Keyboard and Mouse Connector (CN8).....	14
2.4.7 COM Connector (CN9).....	14
2.4.8 LAN and USB 3.0 Connectors (CN11 and CN12).....	15
2.4.9 Audio Jack (CN13)	15
2.4.10 Front Audio Header (CN14)	16
2.4.11 COM Headers (CN15~CN18 and CN44)	16
2.4.12 HDMI Connector (CN20)	17
2.4.13 Internal USB Headers (CN21~CN24)	17
2.4.14 SIM Card Slot (CN25)	17
2.4.15 SATA 3.0 Connectors (CN26~CN30)	18
2.4.16 SMBus Header (CN31)	18
2.4.17 Voltage Monitor Header (CN32).....	18
2.4.18 Power Input Connectors (CN33 and CN34).....	19
2.4.19 PCI-Express x4 Slots (CN39 and CN40)	20
2.4.20 Fan Connectors (CN41~CN43).....	21
2.4.21 VGA Connector (CN45).....	21

Chapter 3	Hardware Description	23
3.1	Microprocessors	23
3.2	BIOS.....	23
3.3	System Memory	23
Chapter 4	AMI BIOS Setup Utility	25
4.1	Starting	25
4.2	Navigation Keys	25
4.3	Main Menu	27
4.4	Advanced Menu	28
4.5	Chipset Menu	41
4.6	Security Menu	45
4.7	Boot Menu.....	46
4.8	Save & Exit Menu.....	47
Appendix A	Watchdog Timer.....	49
B.1	About Watchdog Timer	49
B.2	Sample Program	49
Appendix B	BIOS Flash Utility	51

This page is intentionally left blank.

Chapter 1

Introduction



The IMB500 is an advanced ATX industrial motherboard based on the 6th Generation Intel® Core™ i7/ i5/ i3/ Pentium® and Celeron® processors (Skylake) in LGA1151 Socket with Intel® Q170. The optimized IMB500 is specially designed for better computing and visual performance; ideally used in every major industry for tasks ranging from financial modeling to designing complex buildings and vehicles. With its built-in Intel® HD Graphics 530/510, this industrial grade motherboard delivers great 3D visual performance with triple display capability through DisplayPort, HDMI and VGA ports demanded by professional-grade CAD and media/entertainment fields.

In addition, the IMB500 supports Intel® Turbo Boost 2.0 technology, Intel® Hyper-Threading technology, Intel® HD Graphics with DX11 support, 3-D Tri-Gate transistors, 64GB DDR4 2133/1866MHz memory, and PCI-Express 3.0 x16 slot. It also features Intel® Active Management Technology 9.0 (iAMT), SATA RAID, as well as PCI-Express x4 expansion making it ideal for applications with added security features.

1.1 Features

- LGA1151 Socket 6th Generation Intel® Core™ i7/ i5/ i3, Pentium® and Celeron® processors (Skylake)
- 4 DDR4 2133/1866MHz DIMM with maximum capacity up to 64GB(max. 16GB per slot)
- DisplayPort, HDMI, and VGA with triple view supported
- 5 SATA-600 RAID 0/1/5/10
- 4 USB 3.0 and 8 USB 2.0 ports
- mSATA supported
- PCI-Express Mini Card

1.2 Specifications

- **CPU**
 - LGA1151 Socket 6th Generation Intel® Core™ i7/ i5/ i3, Pentium® and Celeron® processors.
- **Chipset**
 - Intel® Q170.
- **BIOS**
 - AMI BIOS.
- **System Memory**
 - Four 288-pin DIMM sockets.
 - Maximum up to 64GB DDR4 memory(max. 16GB per slot).
 - Support 2133/1866MHz.
- **Onboard Multi I/O**
 - One PS/2 keyboard and mouse.
 - Six serial ports:
 - Four RS-232 (internal box headers).
 - Two RS-232/422/485 (one in rear I/O, and the other in internal box header).
- **USB Interface**
 - Four USB 3.0 ports.
 - Eight USB 2.0 ports.
- **Ethernet**
 - LAN1: 1000/100/10Mbps Gigabit/Fast Ethernet supports Wake-on-LAN, PXE Boot ROM, iAMT with Intel® i219LM.
 - LAN2: 1000/100/10Mbps Gigabit/Fast Ethernet supports Wake-on-LAN, PXE Boot ROM with Intel® i210AT.
- **Serial ATA**
 - Five SATA-600 with RAID 0/1/5/10.
 - One mSATA.
- **Audio**
 - Realtek ALC662 5.1 channel HDA Codec.
 - Support MIC-in/line-in/line-out.

- **Display**
 - One 15-pin D-Sub as VGA connector. Resolution max. up to 1920x1200 @60Hz.
 - One HDMI 1.4b with resolution max. up to 4096x2160 @24Hz.
 - One DisplayPort with resolution max. up to 4096x2304 @60Hz.

- **Expansion Interface**
 - One PCI-Express x16 slot.
 - Two PCI-Express x4 slots.
 - Four PCI slots.
 - One PCI-Express Mini Card.
 - One SIM card slot.

- **Power Input**
 - One ATX power input connector.
 - One 12V ATX power input connector for CPU Power.

- **Operating Temperature**
 - 0°C ~ 60°C.

- **Storage Temperature**
 - -20°C ~ 75°C.

- **Form Factor**
 - 305 x 244mm.



Note


All specifications and images are subject to change without notice.

This page is intentionally left blank.


Chapter 2

Board and Pin Assignments

2.1 Board Layout



2.2 Rear I/O




Jumpers/Headers/Connectors			
1	Internal USB Headers (CN21~CN24)	20	PCI Slots (CN35~CN38)
2	GPIO Header (CN6)	21	mSATA Slot (CN4)
3	Debug Header	22	SATA 3.0 Connectors (CN26~CN30)
4	COM3~COM6 Headers (CN15~CN18)	23	PCI-Express Mini Card Connector (CN3)
5	AT/ATX Mode Select Jumper (JP2)	24	ATX1 Power Input Connector (CN34)
6	Front Panel Header (CN5)	25	DIMM Sockets (DIMM1~DIMM4)
7	SMBus Header (CN31)	26	CPU Socket
8	System Fan Connectors (CN42, CN43)	27	ATX2 CPU Power Input Connector (CN33)
9	Voltage Monitor Header (CN32)	28	PCI-Express x4 Slots (CN39, CN40)
10	CPU Fan Connector (CN41)	29	SIM Card Slot (CN25)
11	COM2 Header (CN44)	30	PCI-Express x16 Slot (CN1)
12	COM2 Mode Select Jumper-1 (JP7)	31	PS/2 Keyboard and Mouse Connector (CN8)
13	COM2 Mode Select Jumpers-2 (JP9, JP10)	32	VGA Connector (CN45)
14	COM2 Data/Power Select Jumper (JP8)	33	COM Connector (CN9)
15	COM1 Mode Select Jumper-1 (JP3)	34	LAN1 and LAN2 Connectors (CN11, CN12)
16	COM1 Mode Select Jumpers-2 (JP5, JP6)	35	Audio Jack (CN13)
17	COM1 Data/Power Select Jumper (JP4)	36	DisplayPort Connector (CN2)
18	Front Audio Header (CN14)	37	HDMI Connector (CN20)
19	Clear CMOS Jumper (JP1)	38	USB 3.0 Connectors (CN11, CN12)



Note

To identify the first pin of a header or jumper, please refer to the following information:

- Usually, there is a thick line or a triangle near the header or jumper pin 1.




- Square pad, which you can find on the back of the motherboard, is usually used for pin 1.



2.3 Jumper Settings

Jumper is a small component consisting of jumper clip and jumper pins. Install jumper clip on 2 jumper pins to close. And remove jumper clip from 2 jumper pins to open. The following illustration shows how to set up jumper.



Before applying power to IMB500 Series, please make sure all of the jumpers are in factory default position. Below you can find a summary table of all jumpers and onboard default settings.



Note

Once the default jumper setting needs to be changed, please do it under power-off condition.

Jumper	Description	Setting
JP1	Clear CMOS Default: Normal Operation	1-2 Close
JP2	AT/ATX Power Mode Select Default: ATX Mode	1-2 Close
JP3/7	COM1/2 RS-232/422/485 Mode Select Default: RS-232	1-2 Close
JP5/9		3-5, 4-6 Close
JP6/10		3-5, 4-6 Close
JP4/8	COM1/2 Data/Power Select Default: RS-232 Data	3-5 Close
		4-6 Close

2.3.1 Clear CMOS (JP1)

This jumper (3x1-pin p=2.54mm) allows you to clear the Real Time Clock (RTC) RAM in CMOS. You can clear the CMOS memory of date, time, and system setup parameters by erasing the CMOS RTC RAM data. The onboard button cell battery powers the RAM data in CMOS, which includes system setup information such as system passwords.

To erase the RTC RAM:

1. Turn OFF the computer and unplug the power cord.
2. Remove the onboard battery.
3. Move the jumper clip from pins 1-2 (default) to pins 2-3. Keep the clip on pins 2-3 for about 5~10 seconds, then move the clip back to pins 1-2.
4. Re-install the battery.
5. Plug the power cord and turn ON the computer.
6. Hold down the key during the boot process and enter BIOS setup to re-enter data.

Function	Setting
Normal operation (Default)	1-2 close
Clear CMOS	2-3 close



2.3.2 AT/ATX Mode Select (JP2)

This 3x1-pin p=2.00mm jumper allows you to select AT or ATX power mode.


Function	Setting
ATX mode (Default)	1-2 close
AT mode	2-3 close



2.3.3 COM1 Mode Select (JP3, JP5, JP6)

Use these jumpers (3x2-pin p=2.54mm) to set COM1 port to operate in RS-232, RS-422 or RS-485 communication mode.


Function	Setting
RS-232 mode (Default)	JP3 1-2 close JP5 3-5, 4-6 close JP6 3-5, 4-6 close
RS-422 mode	JP3 3-4 close JP5 1-3, 2-4 close JP6 1-3, 2-4 close
RS-485 mode	JP3 5-6 close



2.3.4 COM1 Data/Power Select (JP4)

The COM1 port has +5V power capability on DCD# and +12V on RI# by setting this jumper (3x2-pin p=2.54mm).


Function	Setting
Power: Set COM1 pin 1 to +5V	1-3 close
Data: Set COM1 pin 1 to DCD# (Default)	3-5 close
Power: Set COM1 pin 9 to +12V	2-4 close
Data: Set COM1 pin 9 to RI# (Default)	4-6 close



2.3.5 COM2 Mode Select (JP7, JP9, JP10)

Use these jumpers (3x2-pin p=2.54mm) to set COM2 port to operate in RS-232, RS-422 or RS-485 communication mode.


Function	Setting
RS-232 mode (Default)	JP7 1-2 close JP9 3-5, 4-6 close JP10 3-5, 4-6 close
RS-422 mode	JP7 3-4 close JP9 1-3, 2-4 close JP10 1-3, 2-4 close
RS-485 mode	JP7 5-6 close



2.3.6 COM2 Data/Power Select (JP8)

The COM2 port has +5V power capability on DCD# and +12V on RI# by setting this jumper (3x2-pin p=2.54mm).

Function	Setting
Power: Set COM2 pin 1 to +5V	1-3 close
Data: Set COM2 pin 1 to DCD# (Default)	3-5 close
Power: Set COM2 pin 8 to +12V	2-4 close
Data: Set COM2 pin 8 to RI# (Default)	4-6 close



2.4 Connectors


Signals go to other parts of the system through connectors. Loose or improper connection might cause problems, please make sure all connectors are properly and firmly connected. Here is a summary table showing connectors on the hardware.

Connector	Description
CN1	PCI-Express X16 slot
CN2	DisplayPort Connector
CN3	PCI-Express Mini Card Connector
CN4	mSATA Slot
CN5	Front Panel Header
CN6	GPIO Header
CN8	PS/2 Keyboard and Mouse Connector
CN9	COM Connector
CN11, CN12	LAN and USB 3.0 Connectors
CN13	Audio Jack
CN14	Front Audio Header
CN15~CN18, CN44	COM Headers
CN20	HDMI Connector
CN21~CN24	Internal USB Headers
CN25	SIM Card Slot
CN26~CN30	SATA 3.0 Connectors
CN31	SMBus Header
CN32	Voltage Monitor Header
CN33	ATX2 CPU Power Input Connector
CN34	ATX1 24-pin Power Input Connector
CN35~CN38	PCI Slots
CN39, CN40	PCI-Express x4 Slots
CN41	CPU Fan Connector
CN42~CN43	System Fan Connectors
CN45	VGA Connector

2.4.1 DisplayPort Connector (CN2)

The DisplayPort interface is available through CN2.


Pin	Signal	Pin	Signal
1	DP_TX0+	2	GND
3	DP_TX0-	4	DP_TX1+
5	GND	6	DP_TX1-
7	DP_TX2+	8	GND
9	DP_TX2-	10	DP_TX3+
11	GND	12	DP_TX3-
13	GND	14	GND
15	DP_AUX+	16	GND
17	DP_AUX-	18	DP_HPDP
19	GND	20	+3.3V



2.4.2 PCI-Express Mini Card Connector (CN3)

The CN3 complies with PCI-Express Mini Card Spec. V1.2.


Pin	Signal	Pin	Signal
1	PCH_WAKE_N	2	+3.3V_DUAL
3	N/C	4	GND
5	N/C	6	+1.5V
7	+3.3V_DUAL	8	UIM_PWR
9	GND	10	UIM_DAT
11	CLKOUT_PCIE_N3	12	UIM_CLK
13	CLKOUT_PCIE_P3	14	UIM_RST
15	GND	16	UIM_VPP
17	N/C	18	GND
19	N/C	20	RF_KILL#_WIFI
21	GND	22	BUF_PLT_RST_N
23	PCIE7_RX_DN	24	+3.3V_DUAL
25	PCIE7_RX_DP	26	GND
27	GND	28	+1.5V
29	GND	30	SMB_CLK_RESUME
31	PCIE7_TX_DN	32	SMB_DATA_RESUME
33	PCIE7_TX_DP	34	GND
35	GND	36	USB10-
37	GND	38	USB10+
39	+3.3V_DUAL	40	GND
41	+3.3V_DUAL	42	N/C
43	GND	44	N/C
45	CL_CLK	46	N/C
47	CL_DATA	48	+1.5V
49	CL_RST_N	50	GND
51	N/C	52	+3.3V_DUAL



NOTE: screw type is M2*0.4

2.4.3 mSATA Slot (CN4)

Pin	Signal	Pin	Signal
1	N/C	2	+3.3V_DUAL
3	N/C	4	GND
5	N/C	6	+1.5V
7	N/C	8	N/C
9	GND	10	N/C
11	N/C	12	N/C
13	N/C	14	N/C
15	GND	16	N/C
17	N/C	18	GND
19	N/C	20	N/C
21	GND	22	BUF_PLT_RST_N
23	SATA0_RX_DP	24	+3.3V_DUAL
25	SATA0_RX_DN	26	GND
27	GND	28	+1.5V
29	GND	30	SMB_CLK_RESUME
31	SATA0_TX_DN	32	SMB_DATA_RESUME
33	SATA0_TX_DP	34	GND
35	GND	36	USB9-
37	GND	38	USB9+
39	+3.3V_DUAL	40	GND
41	+3.3V_DUAL	42	N/C
43	GND	44	N/C
45	N/C	46	N/C
47	N/C	48	+1.5V
49	N/C	50	GND
51	N/C	52	+3.3V_DUAL




NOTE: screw type is M2*0.4

2.4.4 Front Panel Header (CN5)

This is front panel header (7x2-pin p=2.54mm).

Pin	Signal
1	Power LED+
2	SPK- ^[1]
3	GND
4	BUZZER
5	Power LED-
6	N/C
7	N/C
8	SPK+ ^[1]
9	PWR-
10	PWR+
11	RESET-
12	RESET+
13	HD LED-
14	HD LED+




Note

^[1]: The buzzer on motherboard will be active when pin 2 and pin 4 is connected; the external speaker on chassis will be active when pin 2 and pin 4 is open.

2.4.5 GPIO Header (CN6)

This header (5x2-pin p=2.00mm) is for digital I/O interface.

Pin	Signal	Pin	Signal
1	SIO_GPO74 (0xA06 Bit4, H) ^[1]	2	SIO_GPO70 (0xA06 Bit0, H)
3	SIO_GPO75 (0xA06 Bit5, H)	4	SIO_GPO71 (0xA06 Bit1, H)
5	SIO_GPO76 (0xA06 Bit6, H)	6	SIO_GPO72 (0xA06 Bit2, H)
7	SIO_GPO77 (0xA06 Bit7, H)	8	SIO_GPO73 (0xA06 Bit3, H)
9	GND	10	GND




Note

^[1]: "H" or "L" means the default voltage is High or Low level, and GPIO output is 5V. The GPI or GPO and High or Low level can be selected with BIOS setting.

2.4.6 PS/2 Keyboard and Mouse Connector (CN8)

The motherboard has two 6-pin mini-DIN PS/2 connectors on the rear I/O; green for mouse and purple for keyboard.


Pin	Signal	Pin	Signal
1	KB_DT1	7	MS_DT1
2	N/C	8	N/C
3	GND	9	GND
4	+5V_DUAL	10	+5V_DUAL
5	KB_CK1	11	MS_CK1
6	N/C	12	N/C



2.4.7 COM Connector (CN9)

This is a high rise 9-pin D-Sub connector for COM1 serial port interface. The pin assignments of RS-232/422/485 are listed in table below.

Pin	RS-232 ^[*]	RS-422 ^[*]	RS-485 ^[*]
1	DCD# ^[**]	TX-	485-
2	RXD	TX+	485+
3	TXD	RX+	N/C
4	DTR#	RX-	N/C
5	GND	GND	GND
6	DSR#	N/C	N/C
7	RTS#	N/C	N/C
8	CTS#	N/C	N/C
9	RI# ^[**]	N/C	N/C



Note

^[*]: Signals of COM1 can be RS-232/422/485 by selecting JP3, JP5 and JP6 (see section 2.3.3).


^[**]: Pin 1 of COM1 can be DCD/+5V and pin 9 of COM1 can be RI/+12V by selecting JP4 (see section 2.3.4).

2.4.8 LAN and USB 3.0 Connectors (CN11 and CN12)

The motherboard comes with two high performance plug and play Ethernet interfaces (RJ-45) which are fully compliant with the IEEE 802.3 standard. Connection can be established by plugging one end of the Ethernet cable into this RJ-45 connector and the other end to a 1000/100/10 Base-T hub.

The Universal Serial Bus (compliant with USB 3.0) connectors on the rear I/O are for installing USB peripherals such as keyboard, mouse, scanner, etc.

Pin	LAN Signal	Pin	LAN Signal
L1	Tx+ (Data transmission positive)	L2	Tx- (Data transmission negative)
L3	Rx+ (Data reception positive)	L4	RJ-1 (For 1000 Base-T only)
L5	RJ-1 (For 1000 Base-T only)	L6	Rx- (Data reception negative)
L7	RJ-1 (For 1000 Base-T only)	L8	RJ-1 (For 1000 Base-T only)
A	Active LED	B	Speed LED



Note

- **Speed LED turns orange for 1000Mbps or green for 100Mbps. The light is off for 10Mbps.**
- **CN11 supports AMT when chipset is customized into Intel® Q170. Both CN11 and CN12 support Wake-on-LAN.**

Pin	USB Signal	Pin	USB Signal
1	USB3_POWER	2	USB -
3	USB +	4	GND
5	USB3_SSRX	6	USB3_SSRX+
7	GND	8	USB3_SSTX
9	USB3_SSTX+		

2.4.9 Audio Jack (CN13)

The motherboard provides HD audio jack on the rear I/O. Install audio driver, and then attach audio devices to CN13.


Pin Color	Signal
Green	Line-out
Pink	MIC-in



2.4.10 Front Audio Header (CN14)

This is front audio header (5x2-pin p=2.00mm) for convenient connection and control of audio devices.

Pin	Signal	Pin	Signal
1	MIC_IN	2	GND
3	LINE_IN_L	4	GND
5	LINE_IN_R	6	GND
7	AUD_OUT_L	8	GND
9	AUD_OUT_R	10	GND




2.4.11 COM Headers (CN15~CN18 and CN44)

The motherboard comes with 5x2-pin p=2.54mm headers for COM3~COM6 and COM2 serial port interfaces.

COM3~COM6:

Pin	Signal	Pin	Signal
1	DCD#	2	DSR#
3	RXD#	4	RTS#
5	TXD#	6	CTS#
7	DTR#	8	RI#
9	GND	10	N/C


CN15~CN18



COM2:

Pin	Signal	Pin	Signal
1	DCD# ^[*]	2	DSR#
3	RXD	4	RTS#
5	TXD	6	CTS#
7	DTR#	8	RI# ^[*]
9	GND	10	N/C

CN44




Note

^[*]: Pin 1 of COM2 can be DCD/+5V and pin 8 of COM2 can be RI/+12V by selecting JP8 (see section 2.3.6).

2.4.12 HDMI Connector (CN20)

The HDMI (High-Definition Multimedia Interface) is a compact digital interface which is capable of transmitting high-definition video and high-resolution audio over a single cable.


Pin	Signal	Pin	Signal
1	DATA2+	2	GND
3	DATA2-	4	DATA1+
5	GND	6	DATA1-
7	DATA0+	8	GND
9	DATA0-	10	Clock+
11	GND	12	Clock-
13	N/C	14	GND
15	SCL	16	SDA
17	GND	18	+5V
19	HPD		



2.4.13 Internal USB Headers (CN21~CN24)

These are 5x2-pin p=2.54mm headers for USB 2.0 interface.


Pin	CN21/22/23/24	Pin	CN21/22/23/24
1	+5 V_DUAL	2	+5 V_DUAL
3	USB5/7/11/13-	4	USB6/8/12/14-
5	USB5/7/11/13+	6	USB6/8/12/14+
7	GND	8	GND
		10	N/C



2.4.14 SIM Card Slot (CN25)

The CN25 is for inserting SIM Card.


Pin	Signal	Pin	Signal
1	PWR_UIM	6	DAT_UIM
2	REST_UIM	7	VPP_UIM
3	CLK_UIM	8	GND



2.4.15 SATA 3.0 Connectors (CN26~CN30)

These Serial Advanced Technology Attachment (Serial ATA or SATA) connectors are for SATA 3.0 interface allowing up to 6.0Gb/s data transfer rate. It is a computer bus interface for connecting to devices such as hard disk drive.


Pin	Signal
1	GND
2	SATA_TX+
3	SATA_TX-
4	GND
5	SATA_RX-
6	SATA_RX+
7	GND



2.4.16 SMBus Header (CN31)

The CN31 (5x1-pin p=2.00mm) is for SMBus (System Management Bus) interface.

Pin	Signal	Pin	Signal
1	SMB_SCL	2	N/C
3	GND	4	SMB_SDA
5	+5V		



2.4.17 Voltage Monitor Header (CN32)

The CN32 (8x1-pin p=2.54mm) is for voltage monitoring only. It doesn't supply power.

Pin	Signal	Pin	Signal
1	GND	2	GND
3	VCC5_SB	4	+3.3V
5	-5V	6	+5V
7	-12V	8	+12V




2.4.18 Power Input Connectors (CN33 and CN34)

Steady and sufficient power can be supplied to all components on the motherboard by connecting power connector. Please make sure all components and devices are properly installed before connecting the power connector.

External power supply plug fits into this connector in only one orientation. Properly press down power supply plug until it completely and firmly fits into this connector. Loose connection may cause system instability.


ATX2 CPU power input connector:

Pin	CN33 Signal	Pin	CN33 Signal
1	GND	5	+12V
2	GND	6	+12V
3	GND	7	+12V
4	GND	8	+12V



ATX1 24-pin power input connector:

Pin	CN34 Signal	Pin	CN34 Signal
1	3.3V	13	3.3V
2	3.3V	14	-12V
3	GND	15	GND
4	+5V	16	PS_ON
5	GND	17	GND
6	+5V	18	GND
7	GND	19	GND
8	PWR OK	20	-5V
9	5VSB	21	+5V
10	+12V	22	+5V
11	+12V	23	+5V
12	3.3V	24	GND



2.4.19 PCI-Express x4 Slots (CN39 and CN40)

This motherboard has two PCI-Express x4 slots.


Pin	Signal	Pin	Signal
B1	+12V_PS	A1	GND
B2	+12V_PS	A2	+12V_PS
B3	+12V_PS	A3	+12V_PS
B4	GND	A4	GND
B5	SMB_CLK_RESUME	A5	N/C
B6	SMB_DATA_RESUME	A6	N/C
B7	GND	A7	N/C
B8	+3.3V_PS	A8	N/C
B9	N/C	A9	+3.3V_PS
B10	+3.3V_SB	A10	+3.3V_PS
B11	PCH_WAKE_N	A11	PWRGD
B12	N/C	A12	GND
B13	GND	A13	CLKOUT_PCIE_P5
B14	PCIE1_SLOT1_TX_DP_C	A14	CLKOUT_PCIE_N5
B15	PCIE1_SLOT1_TX_DN_C	A15	GND
B16	GND	A16	PCIE1_SLOT1_RX_DP_C
B17	PCIEX4_SLOT1_PRSENT2_N	A17	PCIE1_SLOT1_RX_DN_C
B18	GND	A18	GND
B19	PCIE2_TX_DP	A19	N/C
B20	PCIE2_TX_DN	A20	GND
B21	GND	A21	PCIE2_RX_DP
B22	GND	A22	PCIE2_RX_DN
B23	PCIE3_TX_DP	A23	GND
B24	PCIE3_TX_DN	A24	GND
B25	GND	A25	PCIE3_RX_DP
B26	GND	A26	PCIE3_RX_DN
B27	PCIE4_TX_DP	A27	GND
B28	PCIE4_TX_DN	A28	GND
B29	GND	A29	PCIE4_RX_DP
B30	N/C	A30	PCIE4_RX_DN
B31	N/C	A31	GND
B32	GND	A32	N/C

2.4.20 Fan Connectors (CN41~CN43)

This motherboard has three fan connectors. Find fan speed option(s) at BIOS Setup Utility: Advanced\HW Monitor\PC Health Status.

The CN41 (4x1-pin p=2.54mm) is for CPU fan connector.

Pin	Signal
1	GND
2	+12V
3	FAN Speed Detection
4	FAN Speed Control



The CN42 and CN43 (4x1-pin p=2.54mm) are for system fan connectors.


Pin	Signal
1	GND
2	+12V
3	FAN Speed Detection
4	FAN Speed Control



2.4.21 VGA Connector (CN45)

This is a high rise 15-pin D-Sub connector which is commonly used for VGA display. This VGA interface configuration can be configured via software utility.

Pin	Signal	Pin	Signal
1	Red	2	Green
3	Blue	4	NC
5	GND	6	DETECT
7	GND	8	GND
9	VCC	10	GND
11	NC	12	DDC DATA
13	Horizontal Sync	14	Vertical Sync
15	DDC CLK		



This page is intentionally left blank.

Chapter 3

Hardware Description

3.1 Microprocessors

The IMB500 Series supports Intel® Core™ i7/ i5/ i3, Pentium® and Celeron® processors, which enable your system to operate under Windows® 7 32/64-bit, Windows® 8.1, Windows® 10 and Linux environments. The system performance depends on the microprocessor. Make sure all correct settings are arranged for your installed microprocessor to prevent the CPU from damages.

3.2 BIOS

The IMB500 Series uses AMI Plug and Play BIOS.

3.3 System Memory

The IMB500 supports four 288-pin DDR4 DIMM sockets for maximum memory capacity up to 64GB DDR4 SDRAMs. The memory module comes in sizes of 2GB, 4GB, 8GB and 16GB.

This page is intentionally left blank.

Chapter 4

AMI BIOS Setup Utility

The AMI UEFI BIOS provides users with a built-in setup program to modify basic system configuration. All configured parameters are stored in a flash chip to save the setup information whenever the power is turned off. This chapter provides users with detailed description about how to set up basic system configuration through the AMI BIOS setup utility.

4.1 Starting

To enter the setup screens, follow the steps below:

1. Turn on the computer and press during the Power On Self Test (POST) to enter BIOS setup, otherwise, POST will continue with its test routines.
2. Once you enter the BIOS, the main BIOS setup menu displays. You can access the other setup screens from the main BIOS setup menu, such as the Advanced and Chipset menus.



Note

If your computer cannot boot after making and saving system changes with BIOS setup, you can restore BIOS optimal defaults by setting JP1 (see section 2.3.1).

It is strongly recommended that you should avoid changing the chipset's defaults. Both AMI and your system manufacturer have carefully set up these defaults that provide the best performance and reliability.

4.2 Navigation Keys

The BIOS setup/utility uses a key-based navigation system called hot keys. Most of the BIOS setup utility hot keys can be used at any time during the setup navigation process. These keys include <F1>, <F2>, <Enter>, <ESC>, <Arrow> keys, and so on.




Note

Some of the navigation keys differ from one screen to another.

Hot Keys	Description
→← Left/Right	The Left and Right <Arrow> keys allow you to select a setup screen.
↑↓ Up/Down	The Up and Down <Arrow> keys allow you to select a setup screen or sub screen.
Enter	The <Enter> key allows you to display or change the setup option listed for a particular setup item. The <Enter> key can also allow you to display the setup sub screens.
+– Plus/Minus	The Plus and Minus <Arrow> keys allow you to change the field value of a particular setup item.
F1	The <F1> key allows you to display the General Help screen.
F2	The <F2> key allows you to Load Previous Values.
F3	The <F3> key allows you to Load Optimized Defaults.
F4	The <F4> key allows you to save any changes you have made and exit Setup. Press the <F4> key to save your changes.
Esc	The <Esc> key allows you to discard any changes you have made and exit the Setup. Press the <Esc> key to exit the setup without saving your changes.

4.3 Main Menu

When you first enter the setup utility, you will enter the Main setup screen. You can always return to the Main setup screen by selecting the Main tab. System Time/Date can be set up as described below. The Main BIOS setup screen is shown below.



BIOS Information

Display the BIOS information.

System Date/Time

Use this option to change the system time and date. Highlight System Time or System Date using the <Arrow> keys. Enter new values through the keyboard. Press the <Tab> key or the <Arrow> keys to move between fields. The date must be entered in MM/DD/YY format. The time is entered in HH:MM:SS format.

Access Level


Display the access level of current user.

4.4 Advanced Menu

The Advanced menu also allows users to set configuration of the CPU and other system devices. You can select any of the items in the left frame of the screen to go to the sub menus:


- ▶ Super IO Configuration
- ▶ Hardware Monitor
- ▶ Fan Function
- ▶ ACPI Settings
- ▶ Trusted Computing
- ▶ CPU Configuration
- ▶ SATA And RST Configuration
- ▶ PCH-FW Configuration
- ▶ AMT Configuration
- ▶ USB Configuration
- ▶ IT8786 GPIO Configuration
- ▶ Serial Port Console Redirection
- ▶ Utility Configuration

For items marked with “▶”, please press <Enter> for more options.



- **Super IO Configuration**

You can use this screen to select options for the Super IO Configuration, and change the value of the selected option. A description of the selected item appears on the right side of the screen. For items marked with “▶”, please press <Enter> for more options.




Serial Port 1~6 Configuration

Use these items to set parameters related to serial port 1~6.

- **Hardware Monitor**


This screen monitors hardware health status.



This screen displays the temperature of system and CPU, cooling fans speed in RPM and system voltages (VCC_CPU, DDR, +12V, +5V and +3.3V).

- **Fan Function**


This screen allows you to select CPU and system fan mode.



CPU_Fan1/Smart Fan 2/Smart Fan 3 Mode

These items allow you to select CPU and system fans mode, which can be set to Full on, Manual and Automatic Mode.

- **ACPI Settings**



ACPI Sleep State

Select the ACPI (Advanced Configuration and Power Interface) sleep state. Configuration options are Suspend Disabled and S3 (Suspend to RAM). The default is S3 (Suspend to RAM); this option selects ACPI sleep state the system will enter when suspend button is pressed.

- **Trusted Computing**

You can use this screen for TPM (Trusted Platform Module) configuration. It also shows current TPM status information.




Security Device Support

Enable or disable BIOS support for security device.

- **CPU Configuration**

This screen shows CPU information, and you can change the value of the selected option.



Hyper-threading


Enable or disable Hyper-threading Technology, which allows a single physical processor to multitask as multiple logical processors. When disabled, only one thread per enabled core is enabled.

Intel Virtualization Technology

Enable or disable Intel Virtualization Technology. When enabled, a VMM (Virtual Machine Mode) can utilize the additional hardware capabilities. It allows a platform to run multiple operating systems and applications independently, hence enabling a single computer system to work as several virtual systems.

- **SATA and RST Configuration**

During system boot up, the BIOS automatically detects the presence of SATA devices. In the SATA Configuration menu, you can see the currently installed hardware in the SATA ports.



SATA Controller(s)


Enable or disable the SATA Controller feature. The default is Enabled.

SATA Mode Selection

Determine how SATA controller(s) operate. Operation mode options are IDE and AHCI (Advanced Host Controller Interface) Mode. The default is AHCI Mode.


- **PCH-FW Configuration**

This screen displays ME Firmware information.



- **AMT Configuration**


Use this screen to configure AMT parameters.



AMT BIOS Features

Enable or disable Active Management Technology BIOS features. The default is Enabled.

- **USB Configuration**




USB Devices

Display all detected USB devices.


- **IT8786 GPIO Configuration**

You can use this screen to set input/output and high/low for each port.



- **Serial Port Console Redirection**

You can use this screen to select options for Serial Port Console Redirection, and change the value of the selected option. A description of the selected item appears on the right side of the screen. For items marked with “▶”, please press <Enter> for more options.




Console Redirection

Enable or disable COM port console redirection.

Console Redirection Settings

Specify how the host computer and the remote computer (which the user is using) will exchange data. Both computers should have the same or compatible settings.

- **Utility Configuration**



BIOS Flash Utility


BIOS flash utility configuration. For more detailed information, please refer to Appendix B.

4.5 Chipset Menu

The Chipset menu allows users to change the advanced chipset settings. You can select any of the items in the left frame of the screen to go to the sub menus:


- ▶ System Agent (SA) Configuration
- ▶ PCH-IO Configuration

For items marked with “▶”, please press <Enter> for more options.



- **System Agent (SA) Configuration**

This screen allows users to configure System Agent (SA) parameters. For items marked with “▶”, please press <Enter> for more options.




Graphics Configuration

Open sub menu for parameters related to graphics configuration.

Memory Configuration

Open sub menu for information related to system memory.

- **Graphics Configuration**




Primary IGFX Boot Display

Select the video device which will be activated during POST (Power-On Self Test). The default is Auto.


- **Memory Configuration**

This screen shows system memory information.



- **PCH-IO Configuration**

This screen allows you to set PCH parameters.



PCH LAN Controller

Enable or disable onboard PCH LAN controller.

Wake on LAN Enable

Enable or disable integrated LAN to wake the system.

4.6 Security Menu


The Security menu allows users to change the security settings for the system.



- Administrator Password**
 This item indicates whether an administrator password has been set (installed or uninstalled).
- User Password**
 This item indicates whether a user password has been set (installed or uninstalled).

4.7 Boot Menu


The Boot menu allows users to change boot options of the system.



- Setup Prompt Timeout**
 Number of seconds to wait for setup activation key. 65535(0xFFFF) means indefinite waiting.
- Bootup NumLock State**
 Use this item to select the power-on state for the keyboard NumLock.
- Quiet Boot**
 Select to display either POST output messages or a splash screen during boot-up.
- Launch PXE OpROM policy**
 Use this item to enable or disable the boot ROM function of the onboard LAN chip when the system boots up.
- Boot Option Priorities**
 These are settings for boot priority. Specify the boot device priority sequence from the available devices.

4.8 Save & Exit Menu

The Save & Exit menu allows users to load your system configuration with optimal or fail-safe default values.



- Save Changes and Exit**
 When you have completed the system configuration changes, select this option to leave Setup and return to Main Menu. Select Save Changes and Exit from the Save & Exit menu and press <Enter>. Select Yes to save changes and exit.
- Discard Changes and Exit**
 Select this option to quit Setup without making any permanent changes to the system configuration and return to Main Menu. Select Discard Changes and Exit from the Save & Exit menu and press <Enter>. Select Yes to discard changes and exit.
- Save Changes and Reset**
 When you have completed the system configuration changes, select this option to leave Setup and reboot the computer so the new system configuration parameters can take effect. Select Save Changes and Reset from the Save & Exit menu and press <Enter>. Select Yes to save changes and reset.
- Discard Changes and Reset**
 Select this option to quit Setup without making any permanent changes to the system configuration and reboot the computer. Select Discard Changes and Reset from the Save & Exit menu and press <Enter>. Select Yes to discard changes and reset.
- Save Changes**
 When you have completed the system configuration changes, select this option to save changes. Select Save Changes from the Save & Exit menu and press <Enter>. Select Yes to save changes.

- **Discard Changes**
Select this option to quit Setup without making any permanent changes to the system configuration. Select Discard Changes from the Save & Exit menu and press <Enter>. Select Yes to discard changes.
- **Restore Defaults**
It automatically sets all Setup options to a complete set of default settings when you select this option. Select Restore Defaults from the Save & Exit menu and press <Enter>.
- **Save as User Defaults**
Select this option to save system configuration changes done so far as User Defaults. Select Save as User Defaults from the Save & Exit menu and press <Enter>.
- **Restore User Defaults**
It automatically sets all Setup options to a complete set of User Defaults when you select this option. Select Restore User Defaults from the Save & Exit menu and press <Enter>.
- **Boot Override**
Select a drive to immediately boot that device regardless of the current boot order.

Appendix A

Watchdog Timer

B.1 About Watchdog Timer

Software stability is major issue in most application. Some embedded systems are not watched by human for 24 hours. It is usually too slow to wait for someone to reboot when computer hangs. The systems need to be able to reset automatically when things go wrong. The watchdog timer gives us solution.

The watchdog timer is a counter that triggers a system reset when it counts down to zero from a preset value. The software starts counter with an initial value and must reset it periodically. If the counter ever reaches zero which means the software has crashed, the system will reboot.

B.2 Sample Program

1. Enter **ADU**, and press <F4> to select the **superior ITE**
2. **PORT** setting **002E**, **002F**
3. Address **07h** setting **07 GPIO**
4. Address **72h** to set the countdown, for example Sec: **C0**, Min: **40**
5. Address **73h** set the countdown time, for example 10sec: **0A**


This page is intentionally left blank.

Appendix B

BIOS Flash Utility

The BIOS Flash utility is a new helpful function in BIOS setup program. With this function you can easily update system BIOS without having to enter operating system. In this appendix you may learn how to do it in just a few steps. Please read and follow the instructions below carefully.


1. In your USB flash drive, create a new folder and name it “Axiomtek”, see figure below.




2. Copy BIOS ROM file (e.g. IMB500.005) to “Axiomtek” folder.




3. Insert the USB flash drive to your system.
4. Enter BIOS setup menu and go to Advanced\Utility Configuration. Select BIOS Flash Utility and press <Enter>.




5. BIOS automatically detect all USB drive(s) attached to the system. In this example only one USB drive is attached to the system. That's why, you can see only one device is displayed in figure below.




6. Select the USB drive containing BIOS ROM file you want to update using the <↑> or <↓> key. Then press <Enter> to get into "Axiomtek" folder.






7. Now you can see the BIOS ROM file on the screen, press <Enter> to select.



8. Select Start to flash system BIOS option to begin updating procedure.



- Please wait while BIOS completes the entire flash update process: erase data, write new data and verify data.



- When you see the following figure, press <Enter> to finish the update process. After that the system will shut down and restart immediately.

